



August 29, 2022

Product Certification

Argos Superbond Mortar Cement Type S Manufactured at our Martinsburg, West Virginia, Plant

Argos certifies that each bag of our Superbond Mortar Cement Type S fully complies with the requirements of ASTM C1329 for a Type S mortar cement.

Superbond Mortar Cement is recommended to be mixed in a mechanical mixer at a volumetric ratio of one cubic foot (1 bag) mortar cement to not less than 2 ¼ and not more than 3 ft³ of damp, loose masonry sand conforming to ASTM C144 and an amount of clean, potable water to produce a workable consistency.

Please note that the property requirements of ASTM C270 are specifically not to be used to determine compliance of mortar strengths or other properties through field-testing (ASTM C270 Section 3.3). For field testing procedures, refer to ASTM C780.

Limited Warranty

Argos warrants that Argos Cements meet applicable ASTM requirements. Argos makes no other warranty, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY of merchantability or fitness for a particular purpose, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. Having no control over their use, Argos will not guarantee finished work in which these products are used.

Sincerely,

Bill Kjollien
Masonry Technical Service Manager
Argos USA LLC
bkjollien@argos-us.com; (404) 307-5992